



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

REC'D 11 JAN 2005

WIPO

PCT

**Bescheinigung**

**Certificate**

**Attestation**

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

**Patentanmeldung Nr. Patent application No. Demande de brevet n°**

03029566.1

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

**R C van Dijk**

BEST AVAILABLE COPY



Anmeldung Nr:  
Application no.: 03029566.1  
Demande no:

Anmeldetag:  
Date of filing: 22.12.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

NESTEC S.A.  
Avenue Nestlé 55  
1800 Vevey  
SUISSE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se referer à la description.)

Depositing device

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

A23G/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

22 Dez. 2003

Depositing device

- This invention relates to the production of food containing gaseous bubbles in a controlled manner. The invention is more particularly related to the depositing of aerated food from pumpable ingredients in which the food can be deposited reproducibly and with more uniform foam characteristics and weight control.
- 10 Methods for producing aerated fat based products are known. For instance, EP 0 322952 B1 relates to aerated ice confections and aerated chilled confections. Chocolate or suitable vegetable fat containing material is melted in a container, tempered and pumped by a pump to a mixer and pressurized CO<sub>2</sub> is supplied to the mixer and the molten chocolate is dispensed by a dispenser having a dispensing valve. When the dispensing device is put in the non-dispensing position, the chocolate is recirculated through a backpressure valve, through
- 20 degasifying means, such as a static mixer, to the container. Accurate control of the amount of product deposited is difficult due to the product velocity in the lines and requires anticipation of the deposited volumes. Furthermore, this process is complex and energy consuming, as it requires a recirculation of the chocolate and degasification of the recirculated chocolate.
- 25 WO 94/19963 relates to a method for dispensing an aerated composition comprising the step of: (a) introducing the composition under pressure into a first volume, (b) allowing the first volume to expand to a second volume at which the pressure of aeration is ambient, and (c) dispensing the second volume of aerated composition.
- 30

WO02/13618 relates to a method for making a cellular food product, by dispersing and/or dissolving under pressure a gas in a food product comprising at least a butterfat, then by expansion to produce cell-formation. The method involves depositing a cellular food product in the form of individual products, or at least strip, whereof the shape is globally preserved as long as it is not subjected to a compression force. The pressure is progressively reduced along the line thereby causing the product to expand before it is deposited.

U.S. Patent 4,637,788 relates to a piston type depositor for depositing an aerated confection wherein at least one outlet valve means is provided that has an annular seat that co-operates with a moveable valve member to control the flow of the liquid-gas mixture; the valve means defining an annular orifice means having a length which is not greater than its diameter. Charging of the valve in product is obtained by allowing the liquid-gas mixture to fill a recess of the valve which is open to the annular orifice. The filled material is then pushed by the piston through the annular orifice. Since product filled in the recess is exposed to atmospheric pressure, it tends to expand rapidly as it enters the recess. The gas-containing confectionery is therefore expanded before being metered out. The action of the metering device deforms the bubbles which were formed in the expansion. Gas cell uniformity and accurate dosing of the product dispensed depends on the regularity and frequency of the piston discharge cycles.

The present invention aims at proposing a solution for depositing a pumpable product which contains gas while

accurately controlling weight and volume of the deposited mass and uniformity of the foam produced.

For that, the invention relates to a depositing device  
5 for depositing flowable food containing gas comprising  
a pressurized feed line conveying flowable food  
containing gas under pressure into the food;  
piston means operatively connected to the feed line  
comprising a piston and a chamber;  
10 an outlet to deliver food at the atmospheric  
pressure into moulds. An improvement of the depositing  
device is to have pressure retaining means arranged with  
the piston means to fill the piston means with pumpable  
product whereas the product in the filled chamber is  
15 maintained at the line pressure. This keeps the food  
under pressure until the point at which it is deposited.  
This largely maintains the gas within the food so that  
the food is not in an aerated form. The bubbles only form  
as the food enters the mould. From then on, there is  
20 less physical action on the bubbles to distort them.  
Therefore, the benefit of maintaining the filled chamber  
at the line pressure is that it ensures the gas remains  
in solution so that the depositing mechanism is dealing  
with a liquid not a foam guaranteeing the correct weight  
25 and volume of product delivered. In other words, the  
gassed product in the chamber is not given the  
possibility to expand in the chamber in an uncontrolled  
manner which would, at the time of depositing in the  
mould leads to dosing accuracy problems, gas pockets or  
30 lack of uniform size distribution of the bubbles.

More particularly, a pressure retaining means is arranged  
to retain the product in the chamber at the same pressure  
as the line pressure and deliver the product through the

outlet as pressure in the chamber increases from the line pressure upon descent of the piston in the chamber. The pressure retaining means ensures that the filled chamber is maintained at super-pressure where the gas remains substantially in the dissolved state of transport but also allows the product to be discharged once the pressure exceeds a certain threshold by the effect of the piston descending into the chamber.

10 The pressure retaining means can be a pressure-actuated valve arranged at the outlet. This solution is simple and reliable. Therefore, the valve automatically opens when the pressure exceeds the line pressure by a certain threshold value. It ensures that the pressure is retained in the piston means which maintains the gas inside the product until the piston means is activated for dispensing, so no specific control of the opening of the valve is necessary. Preferably, the pressure-actuated valve could be a spring-loaded nozzle. Preferably, the valve can be calibrated to open at a pressure of more than 0.5 bars above the line pressure. Therefore, this guarantees that it is only at the point of entry into the mould that the pressure decreases and the chocolate starts to expand.

25 The line pressure may be preferably maintained at a pressure of between 2 to 30 bars, preferably 6 to 15 bars. Therefore, the product delivered to the piston means is always fresh and has the correct quantity of gas.

Another improvement is to have a second valve means which is arranged between the feed line and the chamber and which operates between an opening position wherein the

chamber is filled with flowable food and a closed position wherein the chamber is isolated from the feed line. The second valve means ensures the chamber is hermetically closed after filling while the pressure  
5 inside the chamber is maintained. Therefore, depending on the seal properties of the valve, no gas or, at most, very small amounts of gas can escape out of the chamber back to the feed line when pressure exceeds the feed line pressure once piston starts its descent.

10

In a preferred embodiment, the valve at the feed line has a rotary valve bar comprising at least one passage upon rotation of the valve at a coinciding position between the feed line and the chamber and has a sealing surface  
15 extending along an angular path of at least 90 degrees, preferably 130 degrees, most preferably of 180 degrees. A rotary valve has the advantage to require low force to activate between the open and close position and it furthermore provides an extensive sealing surface that  
20 ensures no gas loss and sedimentation problems. Sediment problems are caused by the solid particles of the chocolate building up between the body or housing and the rotating valve bar.

25 In a preferred embodiment, the invention also relates to a device for producing food containing gaseous bubbles from a pumpable product comprising:

a plurality of depositing devices as aforementioned,  
a feed line for conveying the pumpable product to  
30 the depositing devices,

pump means for providing speed to the pumpable product through the feed line,

a source of gas for incorporating gas into the pumpable product and connected to the feed line,

the pump means being arranged to draw off gas from the gas source and control gas intake into the feed line by the control of the speed of the pump means.

5 As opposed to prior art devices, pump means are disposed for transporting the pumpable product and utilized to regulate the gas intake into the system. More particularly, the pump means comprises a first and second pumps arranged in series along a portion of the feed  
10 line. The line pressure is generated entirely by the first pump whereas the second pump controls the gas flow into the region between the two pumps. In particular, the line pressure is substantially maintained at a constant value from the exit of the first pump to the depositing  
15 devices to ensure that the product does not expand in the line before it is deposited.

The first and second pumps are driven at relative different speeds to create a suction effect within the  
20 portion of the feed line. Therefore, the second pump is driven at a speed higher than the speed of the first pump thereby incorporating gas into the portion of the feed line at a point upstream the second pump. As a result, while the first pump ensures accurate metering of the  
25 pumpable product through the feed line, the second pump regulates more precisely the gas intake into the product. Therefore, control of the gas intake into the pumpable product can be made by controlling the speed of the second pump relative to the speed of the first pump, in  
30 particular, to set the desired quantity of the product coming out of the depositing device. For instance, the ratio of speed of the first pump to the speed of the second pump may be controlled within a range of from 1:1 to 1:5.



The pumps may be of very different types as typically used for transporting flowable liquid and viscous food. Preferably, the pumps are gear pumps, vane pumps, pawl pumps, centrifugal pumps or screw pumps.

5

The invention also relates to a method for aerating and depositing an aerated food comprising

pumping the food from a source of liquefied food,  
adding gas from a source of gas in controlled

10 amounts in the liquefied food to produce a gasified food;  
maintaining a constant pressure of the gasified food  
up to depositing means including retaining means which  
retain the product at said pressure before the depositing  
point to prevent the product from expanding;

15 depositing amounts of the gasified food by forcing  
the product through the depositing point.

Figure 1 is schematic view of the device of the  
invention;

20

Figure 2 is a view of the depositing system;

Figure 3 is a schematic cross-section view of the  
pressure-retaining nozzle in a preferred embodiment;

25

Figure 4 is a bottom view of the nozzle of figure 3.

Referring to Figure 1, a preferred arrangement of the  
device of the invention is shown for gassing and  
30 subsequently depositing at high speed a fat based  
confectionery such as chocolate in a plurality of moulds  
arranged in conveyed rows. The fat based confectionery  
comes in a melted liquid from a kettle 25 transported to  
a temperer 26 by a pump 27. From the temperer, the liquid

product enters the feed line 10 at the beginning of the device of the invention while an excess of product recirculates to the kettle 25 through recirculating line 13. Tempering is a known technique in the manufacturing of chocolate confectionery which aims at inducing the correct polymorphic forms of crystals in the chocolate fat so that when the products cool down, the product sets with the desired shiny and gloss appearance. The temperer is optional and it could be removed from the device of the invention, especially, when considering non-tempering fat-systems such as compounds.

The device comprises a first pump 20 which ensures accurate metering of the confectionery product through the feed line. A second pump 21 is provided along the feed line at a distance from the first pump 20 to delimit with the first pump 20, a portion of tube 11 in-between. A gas source 3 is provided with a gas inlet that communicates with the feed line at some point of the portion of tube 11. The gas source is typically a bottle of compressed gas such as CO<sub>2</sub>, N<sub>2</sub>, N<sub>2</sub>O or O<sub>2</sub> or any other gas compatible with food which will at least partially dissolve under pressure. The outlet of the gas is usually a non-return gas delivery means such as a gas lance comprising a terminal tube with a plurality of openings encased in an outer plastic sleeve. The second pump regulates the gas intake into the product depending upon the speed at which it activates relative to the first pump. When the second pump 21 activates at a speed higher than the first pump, the product is accelerated at the portion of tube 11 which creates a suction effect which draws off more gas from the gas source. As the speed of pump 21 increases, more gas is drawn off in the system. Control of the speed of pump 21 relative to the speed of pump 20 regulates the gas intake at the desired

concentration into the product. Gas flow rate for gassing chocolate component is typically controlled at an even value comprised within a range of from 1 to 50 litres/minutes to deliver a chocolate product having a  
5 density of from 0.5 to 1.1 g/cm<sup>3</sup>.

Therefore, pump 20 is mainly utilized to transport the fat based confectionery at the required pressure, for instance, 5 to 10 bars, and is therefore maintained  
10 constant, whereas the second pump 21 regulates the gas intake. As the second pump runs faster, it reduces the pressure between the two pumps and causes a controlled amount of gas to be introduced. The second pump also prevents the formation of long filaments of gas in the  
15 chocolate.

Of course, it would also be possible to regulate the gas intake between the two pumps by changing the speed of the first pump while maintaining the second pump constant.  
20 However, this would affect the overall pressure and metering of the product in the discharge area which would not be suitable. It is so preferred to control the gas level by adjusting the speed of pump 21 to avoid a negative effect on the metering of the product. It can be  
25 noted that the second pump 21 can act as a coarse preliminary mixer. Gas cells present in the product are broken down into smaller cells and partially dissolved.

The second pump 21 has also the function to ensure there  
30 is no surge of gas as pressure drops in the system after each product discharge from the discharge means. Indeed, as product sequentially discharges, such as by depositing a metered amount of product in moulds, fresh product is drawn into the discharge means, e.g., piston depositing

means, which causes a drop of pressure and consequently more gas drawn. Therefore, the pump 21 being maintained at a controlled higher speed as pump 20, enables to prevent gas surge from happening and to even the gas  
5 intake in the system.

At the exit of the second pump 21, a mixer or beater 4 is preferably installed. This apparatus is useful to provide a finer and more homogeneous distribution of gas in the  
10 confectionery product. As gas is better distributed, the final product also gains in uniformity and weight can be better controlled. The benefit also of the mixer or beater is that mixing is obtained without temperature rise which could create a loss of temper. For this, the  
15 apparatus is actuated at preferably lower speed and has a high surface area to treat a large amount of product at a time. A suitable mixer or beater is for instance, a continuous pins mixer which can treat up to 1000 Kg/hour without using excessive cooling jackets. A pin mixer is  
20 typically formed of an outer stator having static pins that intermesh with dynamic pins of a central rotor. In order to thoroughly mix the gas and the confectionery product together while avoiding the loss of temper, the mixer is preferably driven at a speed of less than 500  
25 rpm, even more preferably between 100 to 300 rpm. When exiting the mixer, the product is usually homogeneously gassed with gas being essentially dissolved homogeneously in the product.

30 The pressure in the line 12 can be advantageously controlled by a pressure transducer 36 that senses the pressure before the depositing device 5. If the pressure exceeds a certain limit, e.g., above a 15-bar limit, the pressure transducer controls the opening of a pressure

sustaining valve 31 in fluid communication with the manifolds of the depositor, and situated at a point above the depositing device, so that the excess of product is sent back to the product kettle 25 via a recirculating  
5 line 14 and until the line pressure is lowered to the desired pressure in the system. This pressure control in combination with the control of the gas intake by the pumps enables to maintain the level of gas dissolved in the product at a substantially constant rate in the line  
10 and so participates to the end benefits on weight control, repeatable and uniform amount of gas in the delivered product.

Figure 2 illustrates a depositing device 5 of the  
15 invention able to deposit a metered amount of gassed product into a conveyed mould. The mould can be empty or, alternatively already partially filled to form layers or a shell, for instance, a chocolate U-shaped shell for receiving a deposited centre of gassed product. The  
20 depositing device 5 of figure 2 shows a single depositing head for reasons of simplicity whereas the depositing device of figure 1 shows a multi-head depositing device 5 which is formed from a plurality of depositing devices 50 of figure 2 placed in parallel and fed by manifolds  
25 connected to the feed line 12.

The depositing device comprises a pressurized manifold 70 to enable product to come into the device. The manifold communicates to a piston arrangement 6 including a piston  
30 or plunger 60 moveably arranged into a product receiving chamber 61. Between the manifold 70 and the piston arrangement is provided a feed channel 71 which opening is selectively controlled by a rotary valve 8. The valve 8 has a form of a cylinder and is housed in the block of

- the manifold and can rotate between a position wherein the channel 71 coincides with a channel 80 of the valve and a position wherein the channel 71 is closed by a cylindrical sealing surface 81. Several channels 80 could  
5 be foreseen in the valve distributed at an angular path of less than 180 degrees but the preferred embodiment is to have only one single channel 80 which delivers a 180-degree sealing surface on each side of the channel.
- 10 The piston arrangement moves towards a depositing outlet which forms a pressure actuated nozzle assembly 9. The pressure actuated nozzle assembly is there to deliver product only at a threshold of product pressure inside the piston means 6. This guarantees that the  
15 confectionery product can only start to expand at the point of entry into the mould and no drips or in flight foamed confectionery remains at completion of the deposit.
- 20 Figure 3 shows a detailed view of the nozzle assembly. The nozzle assembly comprises a spring loaded moving portion of stem 90 that terminates by a sealing portion 91 which co-acts in closure with an abutting portion 93 of a delivery chamber 92. The portion of stem 90 is  
25 housed in an elongated opening 98 of the body 99 of the nozzle which opening has a larger cross-section than the stem to let product pass through.
- At rest, the portion of stem is maintained in a closure  
30 position with the sealing portion 91 abutting against the abutting portion 93 of the chamber by the effect of a resilient element, e.g., a helicoid spring 94, acting against a pressure plate 95 connected to the stem and a fixed part of the body of the nozzle such as an apertured

plate 96. When product is delivered under the pressure of the piston, the product passes through the holes of the plate 96, through the opening 98, until to exert a pressure on the sealing portion 91 at a magnitude that  
5 exceeds the force of the resilient means against the two plates 95, 96 which causes a gap to form between the portions 91 and 93 and product to enter the delivery chamber 92.

10 The nozzle can be equipped with a spreader 97 which splits the stream up from two to ten streams, for instance, four streams 970, 971, 972 and 973 to aid distribution of the confectionery product from the delivery chamber to the mould's cavities.

15 The piston 60 is driven under servo control which enables to deliver more than one shot, i.e., charging the chamber up in one movement and the piston brought down in multiple steps delivering small discrete volumes of  
20 product down to less than 1 gram at high speed. This very precise dosing is rendered possible thanks to the configuration of nozzle and rotary valve which can open and close very reliably at high speed. Speeds up to 40 strokes per minutes can be achieved and up to deliver  
25 circa 160 small discrete shots.

The rotary valve 8 and piston 60 can be electronically or mechanically linked to coordinate the removal of the piston with the opening of the valve. This linkage can be  
30 made by any suitable transmission mechanism that transfers the movement of linear withdrawal of the piston into a rotary movement of the valve in the opening position. This can be done, for instance, by a cam or gear. Alternatively, a central controller can be provided

that coordinates the motion of the valve and the motion of the piston independently.

Example 1:

5 The depositing device of the invention, as illustrated in Figure 1, was compared with a Mondomix aeration system (Haas-Mondomix BV) fitted with a manifold depositor of the type where orifices open for a fixed time to deposit aerated material. The manifold depositor was adjusted to  
10 give the optimum balance of deposits across its width. The two aeration systems were set to aerate with CO<sub>2</sub> at a target density of 0.6 g/cm<sup>3</sup>.

Each system was used to make a number of simple deposits  
15 (without pre-shelling) into mould cavities so as to completely fill them. Then the moulds were weighed to assess the consistency of deposit weight. Different cavity sizes were used for the two depositors as the depositors had been constructed for moulds with different  
20 cavity spacings and volumes. To compare the two systems, the coefficient of variation was calculated by dividing the standard deviation by the mean weight.

154 cavity deposits using the depositor of the invention  
25 were collected and weighed.

Maximum weight	31.14g
Minimum weight	28.69g
Mean weight	31.14g
30 Std Deviation	0.56g
<b>Coefficient of variation</b>	<b>0.018</b>

69 cavity deposits were collected and weighed for the Mondomix with a manifold depositor.



	Maximum weight	109.61g
	Minimum weight	88.83g
	Mean weight	103.22g
5	Std Deviation	3.48g
	<b>Coefficient of variation</b>	<b>0.034</b>

It can be seen by comparing the coefficients of variation  
that the invention leads to improved consistency in  
10 deposit weight.

Claims:

22 Dez. 2003

1. A depositing device for depositing flowable food containing gas comprising
  - 5 a pressurized feed line conveying flowable food containing gas under pressure into the food;  
piston means operatively connected to the feed line comprising a piston and a chamber;  
an outlet to deliver food at the atmospheric
  - 10 pressure into moulds;  
characterized in that it comprises:  
a pressure retaining means arranged to retain the product in the chamber at the same pressure as the line pressure and deliver the product through the outlet as
  - 15 pressure in the chamber increases from the line pressure upon descent of the piston in the chamber.
2. Depositing device according to claim 1, wherein the pressure retaining means is a pressure actuated valve
- 20 arranged at the outlet.
3. Depositing device according to claim 1, wherein the pressure actuated valve is a spring-loaded nozzle.
- 25 4. Depositing device according to claim 2 or 3, wherein the valve is calibrated to open at a pressure of more than 0.5 bar above the line pressure.
- 30 5. Depositing device according to any of the preceding claims, wherein the line pressure is comprised between 2 to 30 bars.
- 35 6. Depositing device according to any of the preceding claims, wherein a valve means is arranged between the feed line and chamber which operates between an opening

position wherein the chamber is filled with flowable food and a closed position wherein the chamber is isolated from the feed line.

5 7. Depositing device according to claim 6, wherein the valve at the feed line has a rotary valve bar comprising at least one passage upon rotation of the valve at a coinciding position between the feed line and the chamber and has a sealing surface extending along an angular path  
10 of at least 130 degrees, preferably of 180 degrees.

8. Depositing device according to claim 1, wherein the outlet has a spreading configuration with a flared and/or splitting zones that splits the stream into a plurality  
15 of streams to aid distribution in wide cavities.

9. Depositing device according to claim 1, wherein the piston is driven under servo control to break down its stroke under multiple steps to deliver discrete volumes  
20 of product at high speed.

10. A device for producing food containing gaseous bubbles from a pumpable product comprising:  
a plurality of depositing devices as any ones of the  
25 preceding claims,  
a feed line for conveying the pumpable product to the depositing devices,  
pump means for providing speed to the pumpable product through the feed line,  
30 a source of gas for incorporating gas into the pumpable product and connected to the feed line,  
the pump means being arranged to draw off gas from the gas source and control gas intake into the feed line by the control of the speed of the pump means.

11. A device according to claim 10, wherein the pump means comprises a first and second pumps arranged in series along a portion of line of the feed line and  
5 wherein the second pump is driven at a speed higher than the speed of the first pump thereby incorporating gas into said portion of line by the effect of suction created by this speed difference.
- 10 12. A device according to claim 11, wherein the line pressure is generated entirely by the first pump.
13. A device according to claim 12, wherein the line pressure is substantially constant from the exit of the  
15 first pump to the depositing devices.
14. A device according to claim 13, wherein the control the gas intake into the pumpable product is made by controlling the speed of the second pump relative to the  
20 speed of the first pump.
15. A device according to claim 14, wherein the ratio of the speed of the first pump to the speed of the second pump is controlled within a ratio ranging of from 1:1.1  
25 to 1:2.
16. A device according to claim 15, wherein the pressure is controlled by a pressure transducer that controls a pressure retaining valve for removing excess of product  
30 from the discharge means.
17. A device according to any ones of claims 10 to 16, wherein the first and second pumps are gear pumps, vane pumps or screw pumps.

18. A method for aerating and depositing an aerated food comprising

- 5        pumping the food from a source of liquefied food,  
      adding gas from a source of gas in controlled  
amounts in the liquefied food to produce a gasified food;  
      maintaining a constant pressure of the gasified food  
up to depositing means including retaining means which  
retain the product at said pressure before the depositing  
10    point to prevent the product from expanding;  
      depositing amounts of the gasified food by forcing  
the product through the depositing point.

15

20

EPO - Munich  
86

22. Dez. 2003

Abstract:

5 The invention is a depositing device for depositing  
flowable food containing gas comprising a pressurized  
feed line conveying flowable food containing gas under  
pressure into the food; piston means operatively  
connected to the feed line comprising a piston and a  
10 chamber; an outlet to deliver food at the atmospheric  
pressure into moulds. The device comprises a pressure  
retaining means arranged to retain the product in the  
chamber at the same pressure as the line pressure and to  
deliver the product through the outlet as pressure in the  
15 chamber increases from the line pressure upon descent of  
the piston in the chamber.

FIG. 1




FIG. 1




FIG. 2



3 / 3




FIG. 3




FIG. 4

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record.**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**